

DH-IPC-HDBW1230E

2MP IR Mini-Dome Network Camera

www.PadVokam.by



- 1/2.7" 2Megapixel progressive CMOS
- H.265 & H.264 dual-stream encoding
- 25/30fps@1080P(1920x1080)
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.8mm fixed lens (3.6mm optional)
- Max IR LEDs length 30m
- IP67, IK10, PoE



System Overview

The IR Megapixel Fixed camera delivers 2MP resolution with a motorized 2.8mm/3.6mm fixed lens. The camera's elegant blend of aesthetics combined with a range of easy mounting solutions provides an excellent choice for a variety of small to mid-size applications at an affordable price.

Functions

Smart Codec (H.265+ & H.264+)

Smart Codec is the optimized implementation of standard video compression (H.265 & H.264) that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart Codec technology reduces bit rate and storage requirements by up to 70% when compared to the standard video compression.

Intelligent Video Analysis (IVS)

Dahua camera is equipped with a built-in intelligent analytic algorithm based on video, which can realize intelligent functions like Tripwire and Intrusion, to quickly and accurately respond to monitoring events in specific area. It can enhance monitoring efficiency. In addition, the camera supports intelligent tamper detection, which is to generate warning message via detecting dramatic scene change and to guarantee effective video surveillance.

Smart IR Technology

With IR illumination, detailed images can be captured in low light or total darkness. The camera's Smart IR technology adjusts the intensity of camera's infrared LEDs to compensate the distance of an object. Smart IR technology prevents IR LEDs from whitening out images as they come closer to the camera. The camera's integrated infrared illumination provides high performance in extreme low-light environments up to 30m (98ft).

Protection (IP67, IK10, wide voltage)

The camera allows for $\pm 25\%$ input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 2KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67) and impact tests (IK10), The camera complies with an IK10 impact rating making it capable of withstanding the equivalent of 5 kg (11.02 lbs) of force dropped from a height of 40 cm (15.75 in.)

Environmental

Dahua cameras operate in extreme temperature environments, rated for use in temperatures from -30°C to $+60^{\circ}\text{C}$ (-22°F to $+140^{\circ}\text{F}$) with 95% humidity.

Image Flip

Capturing unnecessary data such as surrounding hallway walls can increase storage requirements without any added value. The image flip feature allows the camera's image to be rotated in 90° increments for better video optimization.

Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.



Technical Specification					
Camera					
Image Sensor		1/2.7" 2Megapixel progressive CMOS			
Effective Pixels		1920(H)x1080(V)			
RAM/ROM		256MB/32MB			
Scanning System		Progressive			
Electronic Shutter Speed		Auto/Manual, 1/3~1/100000s			
Minimum Illumination		0.08Lux/F2.0(Color,1/3s,30IRE) 0.3Lux/F2.0(Color,1/30s,30IRE) 0Lux/F2.0(IR on)			
S/N Ratio		More than 50dB			
IR Distance		Distance up to 30m(98ft)			
IR On/Off Control		Auto/ Manual			
IR LEDs		24			
Lens					
Lens Type		Fixed			
Mount Type		Board-in			
Focal Length		2.8 mm (3.6 mm optional)			
Max. Aperture		F2.0/F2.0			
Angle of View		H: 104°/92°, V: 55°/50°			
Focus Control		Fixed			
Close Focus Distance		0.6m(0.9m)			
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	40(131ft)	16(52ft)	8(26ft)	4(13ft)
	3.6 mm	53(174ft)	21(69ft)	11(36ft)	5(16ft)
PTZ					
Pan/Tilt Range		Pan: 0° ~355°; Tilt: 0° ~65°; Rotation: 0° ~355°			
Intelligence					
Event Trigger		Motion detection, Video tampering, Scene changing, Network disconnection, IP address conflict, Illegal access, Storage anomaly			
IVS		Tripwire, Intrusion			
Video					
Compression		H.265/H.264H/MJPEG(Sub Stream)			
Smart Codec		Support H.265+/H.264+			
Streaming Capability		2 Streams			
Resolution		1080P(1920×1080)/1.3M(1280×960)/720P(1280×720)/D1(704×576/704×480)/VGA(640×480)/CIF(352×288/352×240)			
Frame Rate		Main Stream: 1080P(1 ~ 25/30fps)			
		Sub Stream: D1(1 ~ 25/30fps)			
Bit Rate Control		CBR/VBR			
Bit Rate		H.265: 12K ~ 6400Kbps H.264: 32K ~ 10240Kbps			

Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / HLC / DWDR
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Electronic Image	Support
Smart IR	Support
Digital Zoom	16x
Flip	0°/90°/180°/270°
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)

Audio	
Compression	N/A
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP;HTTPS;TCP;ARP;RTSP;RTP;RTCP;UDP;SMTP;FTP;DHCP;DNS;DDNS;PPPoE;IPv4/v6;QoS;UPnP;NTP;Bonjour;IEEE 802.1x;Multicast;ICMP;IGMP;TLS
Interoperability	ONVIF Profile S&G, API
Streaming Method	Unicast / Multicast
Max. User Access	10 Users / 20 Users
Edge Storage	NAS Local PC for instant recording
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	Smart PSS, DSS, DMSS
Smart Phone	IOS, Android

Certifications	
Certifications	CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B

Interface	
Video Interface	N/A
Audio Interface	N/A
RS485	N/A
Alarm	N/A

Electrical	
Power Supply	DC12V, PoE (802.3af)(Class 0)
Power Consumption	<5.5W

Environmental

Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Storage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10

Construction

Casing	Metal
Dimensions	Φ109.9mm × 81mm (4.33" x 3.19")
Net Weight	0.34Kg (0.75lb)
Gross Weight	0.47Kg (1.04lb)

Ordering Information

Type	Part Number	Description
2MP camera	DH-IPC-HDBW1230EP-0280B	2MP IR Mini-Dome Network Camera, 2.8mm, PAL
	DH-IPC-HDBW1230EN-0280B	2MP IR Mini-Dome Network Camera, 2.8mm, NTSC
	IPC-HDBW1230EP-0280B	2MP IR Mini-Dome Network Camera, 2.8mm, PAL
	IPC-HDBW1230EN-0280B	2MP IR Mini-Dome Network Camera, 2.8mm, NTSC
	DH-IPC-HDBW1230EP-0360B	2MP IR Mini-Dome Network Camera, 3.6mm, PAL
	DH-IPC-HDBW1230EN-0360B	2MP IR Mini-Dome Network Camera, 3.6mm, NTSC
	IPC-HDBW1230EP-0360B	2MP IR Mini-Dome Network Camera, 3.6mm, PAL
	IPC-HDBW1230EN-0360B	2MP IR Mini-Dome Network Camera, 3.6mm, NTSC
Accessories (optional)	PFA136	Junction box
	PFB203W	Wall mount
	PFA152-E	Pole mount
	PFA200W	Rain Shade

Accessories

Optional:



PFA136
Junction Box



PFB203W
Wall mount



PFA152-E
Pole mount



PFA200W
Rain Shade

Junction Mount	Pole Mount
PFA136	PFB203W + PFA152-E
Wall Mount	Pole Mount with Rain Shade
PFB203W	PFA136+ PFA152-E+PFA200W
Wall Mount with Rain Shade	
PFA136+PFA200W	

Dimensions (mm/inch)

