

DH-IPC-HDBW5231E-ZE

2MP WDR IR Dome Network Camera

www.PadVokam.by



- 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS
- H.265&H.264 triple-stream encoding
- 50/60fps@1080(1920×1080)
- Smart Detection supported
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.7mm ~13.5mm motorized lens
- 1/1 Alarm in/out, 1/1 audio in/out
- Max. IR LEDs Length 50m
- Micro SD memory, IP67, IK10, PoE+



System Overview

With upgraded H.265 encoding technology, Eco-savvy series brings high efficient video compression capability. It can save bandwidth and storage. Meanwhile, the series features starlight, smart IR technology and intelligent image analysis techniques. This series supports reminder function, meanwhile fully protected from dust and water, certified to IP67 and vandal resistant to IK10 standard.

Functions

ePoE technology

The ePoE technology of Dahua, designed internally, adopts advanced 2D-PAM3 coding modulation from physical layer, and realizes full duplex transmission over 800 meters at the speed of 10Mbps, or 300 meters at the speed of 100Mbps via Cat 5 or coaxial cable media. Besides, it supports PoE and PoC power supply technology which has greatly simplified construction and wiring. Dahua ePoE technology offer a new way to accomplish long distance transmission between IP camera and network switch. It allows more flexible surveillance system design, improves reliability and saves construction and wiring cost.

Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low Light Technology offers best-in-class light sensitivity, capturing color details in low light down to 0.006lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, true WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Intelligent Video System (IVS)

IVS is a built-in video analytic algorithm that delivers intelligent functions to monitor a scene for Tripwire violations, intrusion detection, and abandoned or missing objects. A camera with IVS quickly and accurately responds to monitoring events in a specific area. In addition to scene analytics, the camera supports face detection to quickly capture a face and upload the image to a server. The camera also offers tamper detection by recognizing a dramatic scene change and generating a warning message to inspect the camera.

Protection(IP67, IK10, wide voltage)

The camera allows for ±30% input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 6KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67) and impact tests (IK10), the camera is the choice for installation in even the most unforgiving environments.

Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

Technical Specification						Day/Night		Auto(ICR) / Color / B/W	
Camera						BLC Mode		BLC / HLC / WDR(120dB)	
Image Sensor		1/2.8” 2Megapixel progressive scan CMOS				White Balance		Auto/Natural/Street Lamp/Outdoor/Manual	
Effective Pixels		1920(H) x 1080(V)				Gain Control		Auto/Manual	
RAM/ROM		256MB/32MB				Noise Reduction		3D DNR	
Scanning System		Progressive				Motion Detetion		Off / On (4 Zone, Rectangle)	
Electronic Shutter Speed		Auto/Manual, 1/3~1/100000s				Region of Interest		Off / On (4 Zone)	
Minimum Illumination		0.006Lux/F1.4 (Color,1/3s,30IRE) 0.05Lux/F1.4 (Color,1/30s,30IRE) 0Lux/F1.4 (IR on)				Electronic Image Stabilization (EIS)		N/A	
S/N Ratio		More than 50dB				Smart IR		Support	
IR Distance		Distance up to 50m (164ft)				Defog		N/A	
IR On/Off Control		Auto/ Manual				Digital Zoom		16x	
IR LEDs		3				Flip		0°/90°/180°/270°	
Lens						Mirror		Off / On	
						Privacy Masking		Off / On (4 Area, Rectangle)	
Audio									
Compression						G.711a/ G.711Mu/ AAC/ G.726			
Network									
Ethernet						RJ-45 (10/100Base-T)			
Protocol						HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP;NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; RTCP			
Interoperability						ONVIF, PSIA, CGI			
Streaming Method						Unicast / Multicast			
Max. User Access						10 Users / 20 Users			
Edge Storage						NAS Local PC for instant recording Mirco SD card 128GB			
Web Viewer						IE, Chrome, Firefox, Safari			
Management Software						Smart PSS, DSS, Easy4ip			
Smart Phone						IOS, Android			
Certifications									
Certifications						CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B			
Interface									
Video Interface						1 Port(For adjustment only)			
Audio Interface						1/1 channel In/Out			
RS485						N/A			
Alarm						1 channel In: 5mA 5VDC 1 channel Out: 300mA 12VDC			
Electrical									
Power Supply						DC12V, AC24V, PoE+(802.3at)(Class 4)			
Power Consumption						<15W			

Environmental

Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Storage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10

Construction

Casing	Metal
Dimensions	Φ159.1mm×117.9mm (6.26"×4.64")
Net Weight	0.95kg (2.09lb)
Gross Weight	1.20kg (2.65lb)




Ordering Information

Type	Part Number	Description
2MP camera	DH-IPC-HDBW5231EP-ZE	2MP IR Dome NetworkCamera,WDR, PAL
	DH-IPC-HDBW5231EN-ZE	2MP IR Dome Network Camera, WDR,NTSC
	IPC-HDBW5231EP-ZE	2MP IR Dome Network Camera,WDR, PAL
	IPC-HDBW5231EN-ZE	2MP IR Dome Network Camera WDR,NTSC
Accessories (optional)	PFA138	Junction Box
	PFB302S	Wall mount
	PFB201C	In-ceiling mount
	PFB300C	Ceiling mount
	PFA152-E	Pole mount
	PFA101	Mount adapter
	LR1002	ePoE Over Coax Converter

Accessories

Optional:



In-ceiling Mount	Junction Mount	Pole Mount
PFB201C	PFA138	PFA101 + PFB302S + PFA152
		
Ceiling Mount	Wall Mount	
PFA101 + PFB300C	PFA101 + PFB302S	
		

Dimensions (mm/inch)

