

DHL27

27" FHD LCD Monitor

www.PadVokam.by



Features :

- Industrial level LCD panel, suitable for continuous 24/7 operation
- Built-in 3D COMB filter and 3D noise reduction
- High fidelity digital processing for a brilliant and vivid video
- Infrared, RS232 double mode, supporting remote PC control
- Professional thermal design to extend equipment lifespan
- Using tamper-proof metal housing
- Wide array of connectivity options HDMI, DVI, VGA, BNC, USB multimedia, Audio, RS232



Technical Specification

Model

Model	DHL27
-------	-------

Display

Screen Size	27"
Aspect Ratio	16:9
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance	300 cd/㎡
Contrast	1000:1
Display color	16.7M(8bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response Time	14ms
Refresh Rate	60Hz

Signals

Input	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, Audio×1, RJ45(RS232)×1, USB×1	
Output	CVBS(BNC)×2, RJ45(RS232)×1	
Speaker	2W×2	

General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Consumption (Standard)	24W	
Consumption (Standby)	≤1W	
Type	Internal	
Net Weight	7kg (15.4lb)	
Gross Weight	9kg (19.8lb)	
Bezel Width	35.5mm (U/L/R/B)	
Wall Mount	100×100mm (3.9"×3.9")	
Dimension without standard (W×H×D)	669.0×408.0×42.7mm (26.3"×16.1"×1.7")	
Package(W×H×D)	810×555×195mm (31.9"×21.9"×7.7")	
Work Environment	Temperature	0℃~50℃ (32°F~122°F)
	Humidity	20%~90%

Accessory

Standard	VGA cable, power cable, remote control
Optional	Pedestal, hanging bracket

Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

