

## DH-PFM141

### Hi-fidelity Pickup



### Features

- Omni-directional condenser microphone, high fidelity;
- 30KV Air contact ESD, built-in Lightning Protection, power supply polarity reversal protection and electrostatic protection; with ALC, DSP digital noise reduction processing and AGC processing;
- Easy to install, match with cameras or storage devices which have audio function!

### Specifications

| Model                           | DH-PFM141                      |
|---------------------------------|--------------------------------|
| <b>Properties</b>               |                                |
| Scope                           | 5-100m <sup>2</sup>            |
| Sensitivity                     | -32dB(-45~-15dB adjustable)    |
| Frequency response              | 20Hz~20kHz                     |
| Directional characteristic      | Omni-directional               |
| SNR                             | 80dB(1m 40dB sound source SPL) |
| Dynamic range                   | 104dB(1KHz at Max dB SPL)      |
| Max. sustainable sound pressure | 120dB SPL(1KHz, THD 1%)        |
| Output impedance                | 600Ω(non-equilibrium)          |
| Output signal amplitude         | 2.5Vpp/-25dB                   |
| Working voltage                 | DC 12V(9~15V)                  |
| Working current                 | 60mA(50~100mA)                 |
| Working temperature             | -30℃~+70℃                      |
| Color                           | White                          |

# DH-PFM141

|                  |            |
|------------------|------------|
| Outer shell      | PC         |
| Dimension        | φ78mmx26mm |
| Weight           | 73g        |
| Carried standard | CE/FCC     |

## Dimensions (mm)

