

# VTO2000A

IP Villa Outdoor Station

www.PadVokam.by







## Features

- HD CMOS camera
- Stainless steel panel, IP54, IK07
- Night vision & Voice indication
- Video & Audio messaging
- Remote intercom with mobile APP
- Surface mounted & Flush mounted



| Technical Specification |                                                                   |
|-------------------------|-------------------------------------------------------------------|
| Model                   | VTO2000A                                                          |
| System                  |                                                                   |
| Main Processor          | Embedded Micro Processor                                          |
| Operation System        | Embedded LINUX OS                                                 |
| Video                   |                                                                   |
| Video Compression       | H.264                                                             |
| Image Sensor            | 1/3" 1.3MP CMOS                                                   |
| Lens                    | 2.8mm                                                             |
| Angle of View           | D:120° H:90°                                                      |
| Day/Night               | Color Image                                                       |
| Audio                   |                                                                   |
| Audio Compression       | G.711                                                             |
| Audio Input             | Omnidirectional Mic                                               |
| Audio Output            | Built-in Speaker                                                  |
| Bidirectional Talk      | Support Dual-way Bidirectional talk                               |
| Operation Mode          |                                                                   |
| Keypad                  | Single Mechanical Button                                          |
| Interface               |                                                                   |
| Door Control            | 2(1 relay out for main lock, 1 extended by access control module) |
| Alarm In                | 2(1ch unlock button, 1ch feedback)                                |
| RS485                   | 1                                                                 |
| Network                 |                                                                   |
| Ethernet                | 10M/100Mbps Self-adaptive                                         |
| Network Protocol        | TCP/IP                                                            |

|                     |                           |
|---------------------|---------------------------|
| Ethernet            | 10M/100Mbps Self-adaptive |
| Network Protocol    | TCP/IP                    |
| General             |                           |
| Ingress Protection  | IP54, IK07                |
| Tamper Switch       | 1                         |
| Installation        | Surface & Flush           |
| Material            | Stainless Steel           |
| Power               | DC 12V                    |
| Power Consumption   | Standby ≤1W, Work ≤10W    |
| Working Temperature | -40°C~+60°C               |
| Relative Humidity   | 10%~90%RH                 |
| Dimensions          | 129.9mm×32.2mm×140mm      |
| Weight              | 0.8Kg                     |

**Dimensions****Application**