

WV-ASM200 PC Software Package, Release Note

1. Release version: 1.22
2. Release Note Reference Number: ASM200_008

VER (ActiveX VER) Release Date	Priority Rank Level					Contents		
	<div>Priority Rank Level</div> <div>A:Recommend to apply (Major or serious update)</div> <div>B:When issue happened</div> <div>C:Maintenance timing</div> <div>U :Function /Performance improvement (Not Necessary to update)</div>							
		A	B	C	U	Issue (Phenomenon)	Occurrence condition	Correspondence
1.02 (2.0.8.6) Dec. 20, '11	B		X			Unable to download images. (Occurrence frequency : High)	In the case, Administrator name or Password have been changed from factory default "ADMIN", "12345".	Fixed to download properly.
					X	Unable to use 2x digital-zoom function. (Occurrence frequency : High)	When making digital-zoom to "2x " in the case of showing on a monitor that is lower resolution than decoding size. Example: Decode size= 1280x960 Monitor size= 480x360 Notes: It works with no problem in the case Decode size and Monitor sizes are same	Fixed to work properly.
				X		MPEG 4 decoder may stop working (no images are shown) while showing MPEG4 images. (Occurrence frequency : Very read)	Showing MPEG4 images in Live or Playback as usual. No images are shown until receiving next I-frame.	Fixed to show images properly.
				X		M-JPEG image may not be displayed (no images are shown, solid black) while showing frame-advance or frame-reverse playback. (Occurrence frequency : High)	Either frame-advance or frame-reverse playback with displaying enlarge or shrink mode in M-JPEG.	Fixed to show M-JPEG images properly.
1.10 (2.1.3.0) May, '12	C				X	-	-	Supported WV-ASE202 - 25/36/49/64 divided picture (Note: up to 16-picture only for playback). - Supported 25/36/49/64 group configuration (Note: up to 16-picture for sequence). - Supported 4-live-monitor on WV-ASE201 (Total 64 + 4 pictures).
					X	-	-	For WV-ASM200P and E only; - Max recorder: 100 units - Max encoder: 64 units - Max camera: 256 units Up to 4 licenses can be registered.
					X	-	-	For WV-ASM200P and CH only; Up to 10 GXD400 can be controlled.
					X	-	-	Supported auto-tracking function on WV-SC386 and SW396.
				X		Unable to download images from recorder (WJ-HD300 series model) (Occurrence frequency : High)	In a case the administrator's password for WJ-HD300 series model has been changed from "12345" (factory default) to another.	Fixed to download properly even if the administrator's password were changed.
			X			Unable to operate.	If you (user) were a Windows "User" privilege level and WV-ASM200 is version 1.00, 1.02 or 1.10.	Update version 1.10 first. And apply Special dll file. For details, please refer to Service Hint (Technical Information): Order No. AVS1205340T0 S16, W-260 (Windows Privilege Level for the Operator.).
					X			
1.11 (2.1.5.0) Sept., '12	C			X		Video looks blink if sequence were made. (Occurrence frequency : High)	On version 1.10 only (not on ver 1.02). In a case, sequence display between/among multi-screens.	Fixed not to blink.
				X		ASM200 may be crashed. (Occurrence frequency : High)	Occurred event (something fault on devices or network) after once logged-out from ASM200 and logged-in again.	Fixed not to cash ASM200.
				X		While making setup on configuration software, unable to make it with displaying an Input Error (*). (Occurrence frequency : High) *: Message: Cannot register setting information in DB. - Invalid character entry. - No entry. - Invalid value entry.	On version 1.10 only (not on ver 1.02). On configuration software, attempting "Comm"-"FTP mode" to be changed from active to passive.	Fixed to be able to make configuration properly.

WV-ASM200 PC Software Package, Release Note

1. Release version: 1.22
2. Release Note Reference Number: ASM200_008

VER (ActiveX VER) Release Date	Priority Rank Level					Contents		
	A	B	C	U	Issue (Phenomenon)	Occurrence condition	Correspondence	
1.12 (2.1.6.0) Sept., '12	C			X	Noise (strip pattern) on playing back picture. (Occurrence frequency : Low)	In a case playing back at a part of communication error (The noise will be gone by selecting another camera).	Fixed not to display the noise.	
				X	Live picture may be frozen. (Occurrence frequency : High)	In a case disconnecting network and resume connection occurred while using with ASE201 on version 1.10 or 1.11 of ASM200 (does not occur on version 1.02).	Fixed to display live picture, properly.	
				X	Application (ASM200) may crash. (Occurrence frequency : High)	"Down" is set for the shooting direction of the "Dome camera 4" icon at Type in "Camera setup" windows.	Fixed not to crash ASM200.	
1.20 (2.1.6.0) Oct., '12	C			X	Some live pictures may not be displayed (becomes solid black picture) while selecting multi-picture. Example: only 16 pictures at upper-left cornet are displayed out of 64 pictures. (Occurrence frequency : High)	In a case all followings were true; 1. use with ASM200 + ASE201 + ASE202 2. 25-picture or more at live monitor were registered 3. version of ASM200 were "1.12"	Fixed not to display solid black.	
				X	Wrong stream (according to the number of picture before switching by alarm mode instead of the defined single/multi- picture) is selected when switching picture by alarm mode while showing multi-picture on live monitor. Ex.1) In a case 4-picture is shown on live monitor and single- picture is defined in alarm mode, stream 2 will be selected instead of stream 1. Ex.2) In a case single-picture is shown on live monitor and single- picture is defined in alarm mode, stream 2 will be selected instead of stream 1.	In a case all followings were true; 1. Auto mode is selected. 2. ASM200 version 1.10 and newer.	Fixed to workd properly.	
				X	The information history such as ON/OFF status of Camer Groupe in Live monitor was not saved and it restored to the factory default on next activation. (Occurrence frequency : High)	ASM200 version 1.10 and newer.	Fixed saving the information properly and not to restore to the factory default.	
1.22 (2.1.6.0) Jan., '13	C		X		Indication of Rec Status was changed from Red (Recording) to Grey (Rec Pause) while recording. (Occurrence frequency : High)	In a case all followings were true 1. Sequence is activated in recording. 2. ASM200 version 1.10 and newer	Fixed not to change the status infdication.	
			X		Too much jaggy picture. (Occurrence frequency : High)	In a case all followings were true 1. Displaying multi-picture. 2. ASM200 version 1.10 and newer	Fixed not to show jaggy.	
			X		Failed to download MAP data (Occurrence frequency : High)	Retrieved null MAP data and uploaded it.	Fixed null MAP data was prevented from saving.	

Added Jan., '13